


# Non-Spring Return Actuator Nomenclature

LM	C	B	24	-3	-T
<b>Torque Rating</b> GM/GR = 360 in-lb AM/AR = 180 in-lb** NM/NR = 90 in-lb** LM/LR = 45 in-lb** TR = 18 in-lb SY = industrial actuator - to 31,150 in-lbs	<b>Speed*</b> Q = Quickest Running C = Fast Running No Designation = Normal Speed	<b>Version*</b> B = Basic X = Customized	<b>Power Required*</b> 24 = 24 VAC/DC 100 = 100 to 240 VAC 110 = 120 VAC	<b>Control*</b> -1 = On/Off -3 = On/Off, Floating Point -3-P5 = On/Off, Floating Point w/5 kΩ Feedback -3-P10 = On/Off, Floating Point w/10 kΩ Feedback -SR = 2-10 VDC -PC = 0 to 20 Volt (Phasecut) -MFT = Multi-Function Technology -MFT95 = 0 to 135 Ω	<b>Options</b> -T = Terminal Block* Blank = Cable Version -S = Switch* /300 = 10 ft cable (where noted) /500 = 16 ft cable (where noted) X1 - denotes valve actuator

## Ordering Example



**5** Complete Ordering Example: LMCB24-3-T

\*Note: All functions and packaging are not available with all versions

\*\*Note: Q versions have a slightly lower torque rating.