


## Spring Return Actuator Nomenclature

A	F	B	24	-MFT	-S	
<b>Torque Rating</b> A = 180 in-lb† A = 133 in-lb†† N = 90 in-lb L = 35 in-lb T = 18 in-lb	<b>Actuator Type</b> F = Spring Return	<b>Options</b> Blank = None A = No Position Feedback B = Basic C = Fast Running X = Customized	<b>Power Supply</b> 24 = 24 VAC/DC* 120 = 120 VAC** 230 = 230 VAC UP = 24 to 240 VAC***	<b>Control</b> Blank = On/Off -3 = Floating Point -SR = 2-10 VDC -PC = 0 to 20 Volt (Phasecut) -ECON-RO3 = 3 k $\Omega$ NTC Type 10 Thermistor -MFT = Multi-Function Technology -MFT95 = 0 to 135 $\Omega$ -MFT-20 = 6 to 9 VDC 20 VDC Power Supply	-S = Built-in Auxiliary Switch US	

† Available on AFBUP(-S), AFXUP(-S), AFB24-MFT(-S), AFB24-MFT95, AFX24-MFT(-S) or AFX24-MFT95 series only  
 †† Not available with MFT(-S) or MFT95.

\*TF24-3(-S) US is 24 VAC only.  
 \*\*TF series has 100 to 240 VAC nominal power supply.  
 \*\*\*24 to 125 VDC

## Ordering Example



**5** Complete Ordering Example: AFB24-MFT-S

\* All functions and options are not available with all versions